




Check valve type 561 PVC-U With threaded sockets Rp

Model:

- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360



Rp (inch)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FKM Code	SP	Weight (kg)
3/8	10	10	190	161 561 021	1	0.130	161 561 031	1	0.130
1/2	15	10	180	161 561 022	1	0.130	161 561 032	1	0.130
3/4	20	10	380	161 561 023	1	0.260	161 561 033	1	0.280
1	25	10	460	161 561 024	1	0.300	161 561 034	1	0.300
1 1/4	32	10	850	161 561 025	1	0.510	161 561 035	1	0.520
1 1/2	40	10	1080	161 561 026	1	0.780	161 561 036	1	0.790
2	50	10	1670	161 561 027	1	1.390	161 561 037	1	1.400
2 1/2	65	10	2950	161 561 028	1	3.800	161 561 038	1	3.820
3	80	10	3600	161 561 029	1	5.160	161 561 039	1	5.180
4	100	10	4150	161 561 030	1	8.140	161 561 040	1	8.180

Rp (inch)	D (mm)	L (mm)	L2 (mm)	z (mm)
3/8	50	95	56	69
1/2	50	100	56	67
3/4	58	114	65	78
1	68	127	71	85
1 1/4	84	146	85	100
1 1/2	97	152	89	106
2	124	177	101	121
2 1/2	166	233	136	144
3	200	254	141	151
4	238	301	164	174

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>