



Gomiti a 45° ABS metrico

- >d225 - temperatura max d'esercizio: +40°C

d (inch)	d (mm)	PN (bar)	Codice	SP	Peso (kg)	pollici equiv. (inch)	z (mm)	D (mm)	L (mm)
	20	16	729 150 106	10	0,009	½	5	25	21
	25	16	729 150 107	10	0,013	¾	6	31	25
	32	10	729 150 108	10	0,026	1	8	40	30
	40	10	729 150 109	10	0,044	1 ¼	10	49	36
	50	10	729 150 110	5	0,079	1 ½	12	61	43
	63	10	729 150 111	10	0,143	2	14	76	52
2 ½	75	10	729 150 112	5	0,225	2 ½	17	89	61
	90	10	729 150 113	4	0,363	3	20	107	71
	110	10	729 150 114	10	0,567	4	28	131	89
5	140	10	729 150 116	1	1,175	5	32	162	108
	160	10	729 150 117	4	1,713	6	36	185	122
	200	10	729 150 119	1	2,546	8	43	225	149
	225	10	729 150 120	1	3,162	8	49	250	168
	250	6	729 150 121	1	6,139	9	60	282	192
	280	6	729 150 122	1	10,500	10	66	318	213
	315	6	729 150 123	1	14,600	12	74	356	239

I dati tecnici non sono vincolanti. Non comportano alcuna garanzia da parte nostra e sono soggetti a modifiche. Valgono le nostre Condizioni Generali di Vendita.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>